

XES 200

Service station. XES 200.


The all-rounder that complements your edge banding machine or CNC with powerEdge for easy processing of PUR and EVA glue. The properties of PUR glue mean that there are a number of challenges involved in processing. In particular, the challenge begins with extended interruptions in work, such as overnight or over the weekend. But we are offering you three solutions in one machine to make sure you are well-equipped for storage, handling and glue tank cleaning.

Your benefits at a glance:

Storage of the glue application units in a vacuum — delays the bonding time so that the PUR glue does not harden.

Timely preheating of the glue application unit — minimizes the amount of time lost when replacing the container

Automatic running of the emptying process during cleaning or glue change — avoids interrupting production on the edge banding machine



More info
you will find on
www.homag.com

Service station. XES 200.

FEATURES:

- Holding device for **two application units**
- Electronic **temperature regulation** for one application unit, including application roller drive unit
- Two vacuum containers for storing two glue application units or interchangeable containers for a 2.5 kg/h PUR melting unit
- Only compressed air and electricity are required
- Station can be **moved** and can be **universally** and **flexibly** attached to the desired edge banding machines
- **Small** and **compact**, requiring a space of less than 1 m²



Technical data:

Length	860 - 980 mm
Width	600 mm
Height	1.497 mm
Working height	653 mm
Suction power	362 m ² /H
Weight	230 kg
Electrical connection	2,5 kW
Pneumatic connection	6 bar
Air requirement	120 NI/min

